# Northwoods Man

When designer Terry Albers was asked to design a "manly" quilt her thoughts turned to a woodsy color scheme. The result surely is worthy of a leather recliner. (but please, hold the stuffed bear.)



Finished Size: 70" × 86"
Finished Blocks: 18 (10") blocks

#### **MATERIALS**

**NOTE:** Fabrics in the quilt shown are from the Northwoods Marblehead collection by Ro Gregg for Paintbrush Studio/Fabri-Quilt.

- 2¾ yards brown stripe for blocks and border #2
- 1¾ yards dark brown print for setting triangles and sashing
- 2¼ yards brown print for outer border and binding
- 1 ½ yards black print for borders #1 and #3
- 5¼ yards backing fabric Twin-size quilt batting

QUILT DESIGNED AND MADE BY **Terry Albers.** MACHINE QUILTED BY **Diana Napier**.



Terry Albers began writing patterns for her students while teaching at her sister's quilt shop. She now has a line of patterns and has authored three books with her friend Pam Puyleart of Cottage Creek Quilts.



For more information about Terry Albers, go to www.FonsandPorter.com/designers




# **CUTTING**

Measurements include ¼" seam allowances.

#### From brown stripe, cut:

• 12 (5½"-wide) strips. Stack 4 strips with right sides up, matching stripes. Make 3 stacks. From each stack of strips, cut 6 sets of 4 identical (5½") squares (*Cutting Diagram*).



# **NOTE:** Keep sets of identical squares together.

• 7 (3"-wide) strips. Piece strips to make 2 (3" × 66½") side border #2 and 2 (3" × 56") top and bottom border #2.

### From dark brown print, cut:

• 2 (20"-wide) strips. From strip, cut 3 (20") squares and 2 (12") squares. Cut 20" squares in half diagonally in both directions to make 12 side setting triangles (2 are extra). Cut 12" squares in half diagonally to make 4 corner setting triangles.

**NOTE:** If fabric has directional design, cut 1 (12") square in half diagonally from lower left to upper right and 1 (12") square in half diagonally from lower right to upper left.

• 10 (1¼"-wide) strips. From strips, cut 2 (1¼" × 32") sashing rectangles and 14 (1¼" × 10½") sashing rectangles. Piece remaining strips if necessary to make 1 (1¼" × 42¾") sashing rectangle.

#### From brown print, cut:


- 4 (6½"-wide) **lengthwise** strips. From strips, cut 2 (6½" × 74") side border #4 and 2 (6½" × 70½") top and bottom border #4.
- 4 (2¼"-wide) **lengthwise** strips for binding.


#### From black print, cut:

• 13 (1¾"-wide) strips. Piece strips to make 2 (1¾" × 71½") side border #3, 2 (1¾" × 64") side border #1, 2 (1¾" × 58½") top and bottom border #3, and 2 (1¾" × 51") top and bottom border #1.

## **BLOCK ASSEMBLY**

- **1.** Lay out 4 matching (5½") squares as shown in *Block Diagrams*. Join into rows; join rows to complete 1 block.
- 2. Make 18 blocks.







**Block Diagram** 

# CORNER UNIT ASSEMBLY

- **1.** Lay out 1 block, 1 (10½"-long) sashing rectangle, 1 corner setting triangle, and 2 side setting triangles as shown in *Corner Unit Diagrams*. Join to complete 1 Corner Unit.
- 2. Make 4 Corner Units.



Corner Unit Diagrams



**NOTE:** When straightening edges, place 13/4" line on ruler on block points.




Quilt Top Assembly Diagram

- **4.** Add black print side border #1 to quilt center. Add black print top and bottom border #1 to quilt.
- **5.** Repeat for borders brown stripe border #2, black print border #3, and brown print border #4.

## **FINISHING**

**1.** Divide backing into 2 (25%-yard) lengths. Cut 1 piece in half lengthwise to make 2 narrow panels. Join 1 narrow

- panel to each side of wider panel; press seam allowances toward narrow panels.
- **2.** Layer backing, batting, and quilt top; baste. Quilt as desired. Quilt shown was quilted with an allover swirl design (Quilting Diagram).
- **3.** Join 2¼"-wide brown print strips into 1 continuous piece for straight-grain French-fold binding. Add binding to quilt. \*\*



**Quilting Diagram**